# Streamfeeder VALUE SERIES

Applications: Mail Processing - Ink Jet Bases - Labeling Bases - Tabber Bases - Folding Machines - Reinforcing Machines





The V-710IJ is for production mailing operations that demand maximum throughput from their ink jet printing, labeling and tabbing bases. The lightweight V-710IJ provides superior feeding to precisely separate and singulate many types and sizes of product. Job setups and changeovers are easily and quickly accomplished. The variable speed, clutch-free motor provides dependable feeding performance. CE certified.

# **Technical Data**

Max product size:305 x 305 mmMin product size:95 x 95 mmProduct Thickness:min 0.076 mm - max 19.1 mmBelt speed:5700 in/minElectrical Requirements:115/230 VAC, 50/60Hz, 3AWeight:18.6 kg

### V-710IJ & S-1750IJ Features

- VARIABLE SPEED DC MOTOR
- ADJUSTABLE FEED BELTS FOR ADDED FEEDING PERFORMANCE
- QUICK SPLIT SHELL DESIGN
- ADVANCING GATE ENABLES MAINTENANCE WITHOUT STOPPING A JOB
- OPTIONAL EXTERNAL RUN INPUT FOR INTEGRATED START/STOP CONTROL



### Model S-1750IJ

The S-1750IJ is for production mailing operations that demand maximum throughput from their ink jet printing, labeling and tabbing bases.

The S-1750IJ is an ideal alternative for integrated shuttle feeders and provides superior feeding to precisely separate and singulate many types and sizes of product onto a transport base. CE certified.

### **Technical Data**

Max product cital	4E7 2 x 204 8 mm
Max product size:	457.2 x 304.8 mm
Min product size:	200 x 76.2 mm
Product Thickness:	min 0.0762 mm - max 6.35 mm
Belt speed:	5700 in/min
Electrical Requirements:	115/230 VAC, 50/60Hz, 3A
Weight:	40.82 kg

# Full range of Streamfeeder products

This shows only a few products from the wide Streamfeeder products range. Call for more detailed information on:

- FEEDERS / DISPENSERS
- BATCH COUNTERS / ACCUMULATORS
- PLACERS / COLLATION SYSTEMS
- TIP-ON SYSTEMS





# Streamfeeder VALUE SERIES

# **Applications:** Mail Processing - Ink Jet Bases - Labeling Bases - Tabber Bases - Folding Machines - Reinforcing Machines



## **Model V-1000**

The V-1000 is the newest generation of continuous feeding technology in the Streamfeeder Value Series. The V-1000 features quick and tool-less setup, quick make-ready, and easy maintenance. It is capable of feeding a wide variety of materials with exceptional alignment qualities. CE certified.

# **Technical Data**

Max product size: 304.8 x 304.8 mm Min product size: 50.8 x 76.2mm Product Thickness: min 0.07 mm - max 25.4 mm Belt speed: 7800 in/min Electrical Requirements: 115/230 VAC, 50/60Hz, 3A Weight: 21.3 kg

# Features of V-1000 & V-2000

- MOVABLE FEED BELTS
- MOVABLE PRODUCT SEPARATORS
- QUICK RELEASE SIDE GUIDES
- **DEALER:**

03-02 UK 05/2011



# Model V-2000

The V-2000 is the next generation of continuous feeding technology in the Streamfeeder Value Series.

The V-2000 features quick and tool-less setup, quick make-ready and easy maintenance. It is capable of feeding a wide variety of materials at high speed with exceptional alignment qualities. CE certified.

# **Technical Data**

Max product size: Min product size: Product Thickness: Belt speed: Weight:

508 x 457.2 mm 50.8 x 76.2mm min 0.0762 mm - max 25.4 mm 7800 in/min Electrical Requirements: 115/230 VAC, 50/60Hz, 3A 40.82 kg

- VARIABLE SPEED DC MOTOR
- UNIVERSAL ELECTRONIC INTERFACE KIT





**HSA Systems Denmark** DK-2740 Skovlunde | +45 4494 0222 || DK-5260 Odense S | +45 6610 3401

> **HSA Systems France** F-93160 Noisy-Le-Grand | +33 1 4815 5050

www.hsasystems.com | mail@hsasystems.com